

## MODEL/PART DESIGNATIONS

| BRAND NAME | DESCRIPTION                     | MODEL - PART NUMBER |
|------------|---------------------------------|---------------------|
| <b>XL1</b> | <b>XL1</b> – Hot, Cold, Ambient | XL1                 |
|            | WSXL1FR00E(XXXXXX)              |                     |

## CONSUMABLES

| FILTER             | REPLACEMENT FREQUENCY  | PART NUMBER  |
|--------------------|------------------------|--------------|
| SEDIMENT FILTER    | 24 MONTHS (20,000 gal) | H17-SD3      |
| PRE-CARBON FILTER  | 24 MONTHS (20,000 gal) | H17-ECS3     |
| RO MEMBRANE (x2)   | 36 MONTHS              | XL12-WRO1280 |
| POST-CARBON FILTER | 24 MONTHS (5,000 gal)  | XL12-MINERAL |
| AIR FILTER         | 36 MONTHS              | AF           |

## SPECIFICATIONS

| ITEM                               | XL1                                                                  |
|------------------------------------|----------------------------------------------------------------------|
| Water Connection                   | 1/4" Quick Connect for both Source and Reject water                  |
| Recommended Service Water Pressure | 50-70psi (0.5-7kgf/cm <sup>2</sup> )                                 |
| Rate Voltage                       | AC 120V/60Hz @ 6.0Amps                                               |
| Power Consumption                  | 1.2A (120W) Cold Water; 500W Hot Tank ; 6.0A (720W) Max              |
| Power Cord                         | 1.9m (6.3ft)                                                         |
| IP Class                           | IPX1                                                                 |
| Climate Class                      | N Class (32°C +/- 1°C) (89.6°F +/- 33.8°F)                           |
| Safety Device                      | Overheating protector. Water Level Detector. Leak Stop Device. Fuse. |
| Hot Tank Capacity                  | 1.1gal (4.2L)                                                        |
| Ambient Tank Capacity              | 2.5gal (9.5L)                                                        |
| Cold Tank Capacity                 | 5gal (18.9L)                                                         |
| Environmental Temperature          | Max: 90°F (32°C) Min: 35°F (2°C)                                     |
| Source Water Temperature           | Max: 90°F (32.2°C) Min: 40°F(4.5°C)                                  |
| Relative Humidity                  | 55% at 78°F(25.5°C)                                                  |
| Refrigerant Gas                    | R134a; 68g(2.39oz)                                                   |
| R134a Pressures                    | 280Psig (19.3bar) High Side, 88Psig (6.1bar) Low Side                |

## SHIPPING SPECIFICATIONS

| <u>ITEM</u>        | <u>XL1</u>                                               |
|--------------------|----------------------------------------------------------|
| Width/Depth/Height | 480mm W x 518mm D x 1740mm H<br>18.9"W x 20.4"D x 68.5"H |
| Weight (dry)       | 155lbs (70.3 kg)                                         |

