

MODEL/PART DESIGNATIONS

BRAND NAME	DESCRIPTION	MODEL - PART NUMBER
<i>i12</i>	<i>i12</i> – Hot, Cold, Ambient, Ice	i12
	Z10561-(YYMMDD)-00(XXX)	

CONSUMABLES

FILTER	REPLACEMENT FREQUENCY	PART NUMBER
SEDIMENT FILTER	6-12 MONTHS	ICESED
PRE-CARBON FILTER	12 MONTHS	ICEPREC
RO MEMBRANE (x2)	TEST TDS REDUCTION AT 12 MONTHS	ICERO
POST-CARBON FILTER	12 MONTHS	ICEPOSTCA
AIR FILTER	2 YEARS	51-0347-1

SPECIFICATIONS

<u>ITEM</u>	<u>i12</u>
Water Connection	¾" Quick Connect
Recommended Service Water Pressure	50-70psi (0.5-7kgf/cm ²)
Rate Voltage	AC 120V/60Hz @ 4.9Amps
Power Consumption	1.2A (120W) Cold Water & Ice Making; 500W Hot Tank ; 6.0A (720W) Max
Power Cord	1.9m (6.3ft)
IP Class	IPX1
Climate Class	N Class (32°C +/- 1°C) (89.6°F +/- 33.8°F)
Safety Device	Overheating protector. Water Level Detector. Leak Stop Device. Fuse.
Hot Tank Capacity	1.2gal (4.6L)
Ambient Tank Capacity	4.5gal (16.9L)
Cold Tank Capacity	1.2gal (4.6L)
Ice Production	44 lbs/day (19.9 kg/day)
Ice Storage Capacity	8.8 lbs (4 kg)
Environmental Temperature	Max: 90°F (32°C) Min: 35°F (2°C)
Source Water Temperature	Max: 90°F (32.2°C) Min: 40°F(4.5°C)
Relative Humidity	55% at 78°F(25.5°C)
Refrigerant Gas	R134a (3.10oz +/-0.03oz)
R134a Pressures	186Psig (12.8bar) High Side, 88Psig (6.1bar) Low Side

SHIPPING SPECIFICATIONS

<u>ITEM</u>	<u>i12</u>
Width/Depth/Height	430mm W x 492mm D x 1490mm H 16.9"W x 19.4"D x 58.7"H
Weight (dry)	118lbs (53.7 kg)

