

MODEL/PART DESIGNATIONS

BRAND NAME	DESCRIPTION	MODEL - PART NUMBER
<i>WL3 IT</i> Counter Top	<i>WL3 IT Counter Top</i> – Cold, Hot, Ambient	WL3IT-MU-HCA
	F-3IT-MU-HCA-UTL111NX-BL-WLU	
	Serial Number Prefix: NC3H345BL	
<i>WL3 IT</i> Tower	<i>WL3 IT Tower</i> – Cold, Hot, Ambient	WL3IT-FS-HCA
	F-3IT-FS-HCA-UTL111NX-BL-WLU	
	Serial Number Prefix: NC1H345BL	

SPECIFICATIONS

<u>ITEM</u>	<u>WL3 IT</u>
Water Connection	¼" Quick Connect
Cold Water Temperature	Cold Water Temperature – Factory Set Point 5°C (41°F) Adjustable - 1.1° - 12.2°C (34° - 54° F.)
Cold Tank Size	Tower: 4 Liters (1.1 Gallons) Counter Top: 2 Liters (.53 Gallons)
Hot Water Temperature	87°C (189°F) Factory Set Point 92°C (198°F) Extra Hot Factory Set Point
Hot Water Manual Reset Overload	105°C (221°F)
Hot Tank Size	1.5 Liters (.40 Gallons)
Recommended Service Pressure	40-60 psi (275-414 kPa) – Use Pressure Regulator
Maximum Service Pressure	100 psi (689 kPa) – Use Pressure Regulator
Rated Service Flow	1.89 Liters per Minute (0.5 gallons per minute)
Environmental Temperature	2° - 37°C (35° - 100°F)
UV Lamp	Tower: 8 Watts Counter Top: 4 Watts
Heater	500 W
Refrigerant Gas	R134a, 38g, 1.34 ounces
R134a Pressures	High (230 psi), Low (90 psi)

SHIPPING SPECIFICATIONS

<u>ITEM</u>	<u>Counter Top</u>	<u>Tower</u>
Width/Depth/Height	38.5cm x 45.2cm x 44.5cm 15.2" x 17.8" x 17.5"	38.5cm x 36.5cm x 114cm 15.2" x 14.4" x 44.9"
Weight (dry)	24 kg (52.9 pounds)	27 kg (59.5 pounds)

#Counter Top is 17.75 in. tall and may not fit between countertops and cabinets - Check installation to ensure adequate clearance.



ELECTRICAL SPECIFICATIONS

ELECTRICAL SUPPLY	120V/60Hz, 1PH	15 Amp Service
COMPONENT	POWER (approximate)	AMP DRAW (approximate)
Heater	504	4.2 Amps
Compressor	216	1.8 Amps
UV Lamp System	18	0.15 Amps
WL3 IT TOTAL	738	6.15 Amps